

520-40/520-50/524-50 TELESCOPIC HANDLER.

1. The vision to succeed

JCB telehandlers benefit from a forward cab position; the resulting all-round visibility helps operators achieve maximum productivity.

2. Full-size cab

Our distinctive low offset boom design allows us to install a proper-sized cab in our Loadalls for high levels of comfort.

3. Simple servicing

We've designed our telehandler range so that all routine servicing and maintenance is easy and efficient.

4. The sum of its parts

For ultimate reliability and performance, we design and build all the key components of these machines, like engines, axles and transmissions.

5. Operator environment

Controls are properly thought-out and ergonomically positioned to reduce operator fatigue. Optional air conditioning helps to create the perfect workplace.

6. Manoeuvrability

Because JCB Loadalls have compact wheelbases and tight steering lock angles, you can operate with speed and efficiency everywhere.





Lift capacity is impressive for such a small machine.



Excellent manoeuvrability in tight spaces.



Lift heights from 4m-5.6m.

	520-40	520-50	524-50
Maximum lift height	m 4.04	5.0	5.3
Maximum lift capacity	kg 2000	2000	2400
Maximum forward reach	m 2.59	2.82	2.9
Lift capacity at full reach	kg 1000	750	1250
Overall height	m 1.97	2.12	2.1
Overall width over tyres	m 1.56	1.84	2.0
Overall length to front carriage	m 3.38	3.59	3.9
Engine (gross)	hp (36.3)	74 (55)	74 (55)